





WWW.FAS.IT



Fas

PR

MAIN FEATURES

Enlarged capacity

Delivery bin and delivery door with enlarged dimensions to ensure the withdrawl of bulky products compared to the normal standard

10" Interface tablet

Interface enduser touchscreen customizeable with logos, videos. Programming iconographic easy and fast.

Intelligent lighting

Power LED at high efficiency with programmable energy saving function; delivery bin illuminated intermittently when product is delivered

Fas Cloud +

Management, programming, updates, cloning and Audit functions on site or from remote via Fas Cloud+

Double Glazed glass with high efficiency

Laminted glass with security and low emission to avoid fogging and condensation

Typical Configurations available

Up to 3 different zone temperatures (Snack/Drink/Food); Lateral air flow to avoid build up condensation (patented)

CO2 Cooling unit monobloc

Refrigeration unit charged with CO2 (GWP=1) with inverter board to control to speed; Fast extraction due to the Slide in - Slide out system (patented)



Efficiency energy rating

TECHNICAL FEATURES

| L.N.; Dimensions and finishing | |
|----------------------------------|-------------------------|
| Number of trays standard/maximum | 6/7 |
| Number of selections | Up to 56 |
| Hieght - Width - Depth | 1830 - 910 - 790 mm |
| Footprint with door open | 1660 mm |
| Weight | 274 Kg |
| Aesthetic finishing | Graphite grey and black |

Electrical data

| Power supply | 230/50-60 V/Hz |
|------------------------------|-------------------------|
| Rated power | 450 W |
| Minimal internal temperature | 3°C with health control |

Amenities

| Protocols | Executive/MDB |
|-------------------------------|---------------|
| Digital Display Trays | Optional |
| Anti-theft bars | Yes |
| Easy Click system | Yes |
| Photocells product delivery | Yes |
| Pre-cooling compartment | Yes |
| WI-FI and bluetooth LE native | Yes |

