



Fas SKUDO



Fas SKUDO

TECHNICAL FEATURES

CO2 Cooling unit monobloc

control to speed; Fast extraction due to the Slide in - Slide out system (patented)x

IP-24 certified



Efficiency energy rating

Linit Dimensions and finishing	
Number of trays standard/maximum	6/7
Number of selections	Up to 70
Hieght - Width - Depth	1845 - 1080 - 865 mm
Footprint with door open	1830mm
Weight	380 Kg
Aesthetic finishing	Graphite grey and black

(4) Electrical data

Power supply	230/50-60 V/Hz
Rated power	450 W
Minimal internal temperature	3°C with health control

Amenities	
Protocols	Executive/MDB
Digital Display Trays	Distributore automatico blindato
Anti-theft bars	Optional
Easy Click system	Yes
Photocells product delivery	Yes
Pre-cooling compartment	Yes
WI-FI and bluetooth LE native	Yes
Fas Cloud +	Yes



MAIN FEATURES

Protection at it's highest levels

Armoured door with 4 locking points con 4 punti di chiusura, antivandalism coin insert and coin return slots, polycarbonate 4mm thickness for the protection of the glass, lexan 5mm for the protection of the tablet and kepad, unscrewable door handle in steel.

Enlarged capacity

Delivery bin and delivery door with enlarged dimensions to ensure the withdrawl of bulky products compared to the normal standard

7" Interface tablet

Interface enduser touchscreen customizeable with logos, videos. Programming iconographic easy and fast.

Intelligent lighting

Power LED at high efficiency with programmable energy saving function; delivery bin illuminated intermittently when product is delivered

Fas Cloud +

Management, programming, updates, cloning and Audit functions on site or from remote via Fas Cloud+

Typical Configurations available

Up to 3 different zone temperatures (Snack/Drink/Food); Lateral air flow to avoid build up condensation (patented)

Refrigeration unit charged with CO2 (GWP=1) with inverter board to